The following Listing of Claims will r eplace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A rotary compressor comprising:

a compression mechanism ~~(20)~~ including a cylinder ~~(21)~~ having a cylinder chamber ~~(C)~~ ~~(C1, C2)~~, a piston ~~(22) accommodated~~ disposed in the cylinder chamber ~~(C)~~ ~~(C1, C2)~~ ~~eccentrically~~ to be eccentric with respect to the cylinder ~~(21)~~, and a blade ~~(23)~~ arranged in the cylinder chamber ~~(C)~~ ~~(C1, C2)~~ and ~~sectioning~~ dividing the cylinder chamber ~~(C)~~ ~~(C1, C2)~~ into a high pressure chamber ~~(C-Hp)~~ ~~(C1-Hp, C2-Hp)~~ and a low pressure chamber ~~(C-Lp)~~ ~~(C1-Lp, C2-Lp)~~, the cylinder ~~(21)~~ and the piston ~~(22)~~ eccentrically rotating relative to each other;

a motor ~~(30) for driving~~ configured to drive the compression mechanism ~~(20)~~; and

a casing ~~(10) for accommodating~~ configured to house the compression mechanism ~~(20)~~ and the motor ~~(30)~~, ~~wherein~~

the casing forming a low pressure space ~~(S1)~~ communicating with a suction side of the compression mechanism ~~(20)~~ and a high pressure space ~~(S2)~~ communicating with a discharge side of the compression mechanism ~~(20) are formed in the casing (10)~~, and

the casing ~~(10) is provided with~~ having a suction pipe ~~(14)~~ connected to ~~the~~ a low pressure space ~~(S1)~~ side of the casing ~~(10)~~ and a discharge pipe ~~(15)~~ connected to ~~the~~ a high pressure space ~~(S2)~~ side thereof.

2. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein

the casing forms two spaces ~~are formed in the casing (10) with~~ and the compression mechanism is ~~(20)~~ interposed therebetween, one of the two spaces is the high pressure space ~~(S1)~~, and the other thereof is the low pressure space ~~(S2)~~.

3. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein the motor ~~(30)~~ is disposed in the high pressure space ~~(S2)~~.

4. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein the high pressure space ~~(S2)~~ is formed below the compression mechanism ~~(30)~~, and an oil sump ~~(19)~~ for accumulating lubrication oil is formed in the high pressure space ~~(S2)~~.

5. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein ~~the~~ an outer peripheral face of the compression mechanism ~~(20)~~ is surrounded by the low pressure space ~~(S1)~~.

6. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein the cylinder chamber ~~(C1, C2) is formed in~~ has an annular ~~shape in section~~ cross section when viewed at a right angle in an axial direction, and

the piston ~~(22)~~ is formed of an annular piston ~~(22)~~ arranged in the cylinder chamber ~~(C1, C2)~~ and sectioning the cylinder chamber ~~(C1, C2)~~ into an outer cylinder chamber ~~(C1)~~ and an inner cylinder chamber ~~(C2)~~.

7. (Currently Amended) The rotary compressor of ~~Claim~~ claim 6, wherein

the blade ~~(23)~~ is formed continuously with the cylinder ~~(21)~~,

the rotary compressor further includes a coupling member ~~(27)~~ through which the annular piston ~~(22)~~ and the blade ~~(23)~~ are movably coupled to each other, and

the coupling member ~~(27)~~ includes a first sliding face ~~(P1)~~ corresponding to the annular piston ~~(22)~~ and a second sliding face ~~(P2)~~ corresponding to the blade ~~(23)~~.

8. (Currently Amended) The rotary compressor of ~~Claim~~ claim 7, wherein

the annular piston ~~(22) has a shape of C obtained by cutting an annular ring~~ is C-shaped to form a gap,

the blade ~~(23)~~ is formed to extend from an inner peripheral wall surface of the annular cylinder chamber ~~(C1, C2)~~ to an outer peripheral wall surface thereof while being inserted through the ~~cut part~~ gap of the annular piston ~~(22)~~, and

the coupling member ~~(27)~~ is a swing ~~bush (27)~~ bushing having an arc-shaped outer peripheral face slidably supported in the ~~cut part~~ gap of the annular piston ~~(22)~~, a blade groove (28) being formed therein for supporting the blade ~~(23)~~ to allow the blade ~~(23)~~ to move back and forth.

9. (Currently Amended) The rotary compressor of ~~Claim~~ claim 6 further comprising

a drive shaft ~~(33) for driving~~ configured to drive the compression mechanism ~~(20)~~, ~~wherein~~

the drive shaft ~~(33) comprises~~ including an eccentric portion ~~(33a)~~ that is eccentric from ~~the~~ a rotation center, the eccentric portion ~~(33a)~~ being coupled to the cylinder ~~(21)~~ or the annular piston ~~(22)~~, and

parts of the drive shaft ~~(33)~~ located ~~to~~ at both longitudinal sides of the eccentric portion ~~(33a)~~ are supported through ~~the~~ a plurality of bearing portions ~~(16a, 17a)~~ in the casing ~~(10)~~.

10. (Currently Amended) The rotary compressor of ~~Claim~~ claim 1, wherein

the cylinder chamber ~~(C)~~ has a circular ~~shape in~~ cross section when viewed at a right angle in an axial direction, and

the piston ~~(22)~~ is formed of a circular piston ~~(22)~~ arranged in the cylinder chamber ~~(C)~~.